

AVENGER 26 4WD (with Agri Tyres)

ENGINE						
Model / Make	S3L2-18.	S3L2-18.2/2500, MHI				
HP Category	26					
Туре	4 cycle, Vertical Overhead Valve, Cylinder in line,					
	Swirl Chamber type					
No. of Cylinders	3					
Bore / Stroke (mm)	78 / 92					
Rated Engine (RPM)	2500					
Displacement (cc)	1319					
Fuel Pump	In-Line Type (ND-PFR M TYPE)					
Air Cleaner Type	Dry with Clogging Sensor					
Cooling System	Water Cooled					
CLUTCH						
Туре	Heavy Duty Dry Type Single Clutch					
Plate Size	Dia 224 mm					
TRANSMISSION						
Gear Box	9F + 3R Constant Mesh					
ROAD SPEED KM/hr	F	FORWARD REVE			EVERS	E
Gear	HIGH	MED	LOW	HIGH	MED	LOW
1	9.19	4.64	1.46	10.63	5.36	1.69
2	12.98	6.55	2.06			
3	21.35	10.78	3.39			
HYDRAULIC SYSTEM						
Туре	Open Center, ADDC					
Hydraulic Pump	Gear Type					
Linkage	TPL Category 1N					
Lifting Capacity (kg)	800					
STEERING						
Туре	Power Steering					
POWER TAKE OFF						
Туре	2 Speeds					
Splines	6					
PTO / Speed	540 @ 2500					

Technical Specifications

CAPACITIES (LITRES)				
Fuel Tank	25			
Engine Sump	3.7			
Cooling System	5.8			
Transmission & Hydraulic	18±10%			
ELECTRICAL INSTALLATION				
Battery	12V, 65Ah			
Alternator	12V, 65A			
Starter Motor	12V, 1.7 KW			
MIN. TURNING RADIUS				
Without Brakes (m)	3.0			
TYRE SIZE	Agriculture Tyre			
Front	6.00 - 12			
Rear	8.3 - 20			
Weight (Kg.)	1260			
FRONT DRIVE AXLE for 4WD Only				
Differential				
Total Ratio	1:13.81			
Oil Capacity (Ltr.)	3.2 Ltr.			
BRAKES				
Type	Multi Disc Oil Immersed			
DIMENSIONS (in mm)	Agriculture Tyre			
Overall Length	2860			
Width	1120			
Height	2230			
Ground Clearance	293			
Wheel Base	1542			
Front Track	860			
Rear Track	820			
Steering wheel height	1398 (from ground)			

For further details please contact nearest dealer

PREET TRACTORS PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA.

Email: info@avenger.co.in | Visit us at: www.avenger.co.in