



EUROPEAN SERIES



POWERED TO PERFORM

AVENGER 26H

HST 4WD

MORE POWER IN LESS FUEL CONSUMPTION • LOW MAINTENANCE COST

TURF


AVENGER 26 HST (with Turf Tyres)

ENGINE		
Model / Make	MVS3L2 / MHI	
HP Category	26	
Type	4 cycle, Vertical Overhead Valve, Cylinder in line, Swirl Chamber type	
No. of Cylinders	3	
Bore / Stroke (mm)	78 / 92	
Rated Engine (RPM)	2500	
Displacement (cc)	1319	
Fuel Pump	In-Line Type (ND-PFR M TYPE)	
Air Cleaner Type	Dry with Clogging Sensor	
Cooling System	Water Cooled	
CLUTCH		
Type	Heavy Duty Dry Type Single Clutch	
Plate Size	Dia 224 mm	
TRANSMISSION		
Gear Box	3F + 3R HST	
ROAD SPEED KM/hr		
	FORWARD	REVERSE
Low	16.36	16.36
Medium	8.26	8.26
High	5.45	5.45
HYDRAULIC SYSTEM		
Type	Open Center, ADDC	
Hydraulic Pump	Gear Type	
Linkage	TPL Category IN	
Lifting Capacity (kg)	800	
STEERING		
Type	Power Steering	
POWER TAKE OFF		
Type	2 Speed	
Splines	6	
PTO / Speed	540 @ 2500	540 E @ 2035

Technical Specifications

CAPACITIES (LITRES)	
Fuel Tank	25
Engine Sump	3.7
Cooling System	5.8
Transmission & Hydraulic	18±10%
ELECTRICAL INSTALLATION	
Battery	12V, 65Ah
Alternator	12V, 65A
Starter Motor	12V, 1.7 KW
MIN. TURNING RADIUS	
Without Brakes (m)	3.0
TYRE SIZE	
Front	23 x 8.50 - 12
Rear	33 x 15.5 - 16.5
Weight (Kg.)	1070
FRONT DRIVE AXLE for 4WD Only	
Differential	
Total Ratio	1:13.81
Oil Capacity (Ltr.)	3.2 Ltr.
BRAKES	
Type	Multi Disc Oil Immersed
DIMENSIONS	
Overall Length	2664
Width	1050
Height	2530
Ground Clearance	320
Wheel Base	1550
Front Track	865
Rear Track	835

For further details please contact nearest dealer



PREET TRACTORS PVT. LTD.

Patiala Road, NABHA-147 201 (Pb.) INDIA.

Email: info@avenger.co.in | Visit us at: www.avenger.co.in

Note : Being continuous development & improvement is our company policy, all products, and product specifications are subject to change without prior notice to improve Reliability, Function or Design or Otherwise.